

A460

AI Conference

Omnidirectional Microphone



The A460 3 omnidirectional conference microphone adopts self-developed new generation AI audio algorithm, integrated intelligent noise reduction and automatic de-reverberation technology, effectively suppressing ambient noise and echo interference, guaranteeing the clarity and stability of voice transmission. Built-in 3 directional microphones for 360° dead-angle sound pickup, supporting efficient sound pickup within 4 meters and up to 8 meters. Built-in 5W high-fidelity speaker, with full sound quality and high degree of reproduction, it also supports full-duplex voice communication and up to 8 levels of master-slave cascade deployment to meet the needs of medium and large conference. Compatible with USB 2.0 plug and play, it supports audio local recording, local efficient summary after the meeting. It is the ideal audio solution for professional-grade remote audio and video conferencing system.

Product Feature

- A new generation of self-research AI intelligent noise reduction and de-reverberation technology
- Full-duplex technology with fully optimized dual-mic
- Automatic gain technology, consistent sound from near and far
- Master-slave multiplexing cascade, support up to 8 levels cascade
- 3 omnidirectional microphone, 360 ° all-round accurate pickup

- 4m effective pickup, 8m furthest pickup
- 5W hi-fi speakers for clear and penetrating vocals
- USB 2.0 Plug and Play
- Audio recording, one-click extraction after the conference

Specification

Item	Function	Description
Microphone	Quantity	3 directional pickup microphones, composed of 360° pickup
	Sound Pick-up	4-meter pickup efficient pickup, 8-meter farthest pickup
	Sampling Frequency	48K HZ sampling (USB) / 16K HZ sampling (Bluetooth)
	SNR	≥60dB
	Maximum Sound Pressure	118dB SPL @ 1KHz, THD<10%
	Full Duplex Audio	Support
Speaker	Power	1x 5W Speaker
	Rated Power	5W/4Ω
	Frequency Response	200Hz - 15KHz
	Volume	84dB SPL, 5w, (1m)
Audio Processing	Echo Cancellation	Support
	Noise Suppression	Support
	Automatic Gain Control	Support
	AI Intelligent Noise Reduction	Support
	Intelligent Reverb Cancellation	Support
Interface	Host	1x USB-C connector, USB 2.0
	Cascade (previous)	1x RJ45 port, cascade to previous level device
	Cascade (next)	1 x RJ45 port, cascade to next level device

	Power Supply	1x DC
	Lock	1x Kensington
Key	Volume - / Mute / Volume + / Audio Record / Bluetooth Key	
Bluetooth	Bluetooth 5.1	
Cascade	Supports 8-level cascade, master-slave multiplexing	
Indicator Bar	The body comes with three (red, green and blue) indicator bands for status indication.	
Battery	Not supported	
Power Supply Method	Power adapter power supply	
System Compatibility	Windows 7/8/10; macOS 10.10 or higher; Linux (requires system support for UAC); Android (general purpose, may be different for each system)	
Working Condition	Storage Temperature: -10°C ~ +70°C Storage Humidity: 20% ~ 95% Operating Temperature: -10°C ~ +50°C Operating Humidity: 20% ~ 80% Operating Environment: Indoor	
Dimensions (L*W*H)	227.87*205.81*63.08mm	

Product Dimension

